

Safety Data Sheet

BOSS® 760 Firestop Silicone

Section 1. Identification

Product Identifier Synonyms Manufacturer Stock Numbers	BOSS® 760 Firestop Silicone 76050; 76029; 76020; 76010 03421RD10; 03478RD17; 03466RD10; 03465RD01; C04073RD		
Recommended use Uses advised against	Refer to Technical Informa Refer to Technical Informa		
Manufacturer Contact Address	Soudal Accumetric 350 Ring Road Elizabethtown, KY, 42701 USA		
	Phone (270) 769-3385	Emergency Phone (800) 424-9300 CHEMTREC	Fax (270) 765-2412

Section 2. Hazards Identification

Classification	EYE DAMAGE/IRRITATION - Category 2A HAZARDOUS TO THE AQUATIC ENVIRONMENT - LONG-TERM HAZARD - Category 3 SENSITIZATION - SKIN - Category 1 SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure) - Category 2
Signal Word	Warning

Pictogram	
Hazard Statements	Causes serious eye irritation Harmful to aquatic life with long lasting effects May cause an allergic skin reaction May cause damage to organsthrough prolonged or repeated exposure.
Precautionary Statements	
Response	Get medical advice/attention if you feel unwell. If eye irritation persists: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If on skin: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Read label before use. Wash contaminated clothing before reuse.
Prevention	Avoid breathing dust/fume/gas/mist/ vapors/spray. Avoid release to the environment Contaminated work clothing must not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/ vapors/spray. Wash hands thoroughly after handling. Wear eye protection/face protection. Wear protective gloves.
Storage	N/A
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Ingredients of unknown toxicity	0%
Hazards not Otherwise Classified Additional Information	None known

Section 3. Ingredients

CAS	Ingredient Name	Weight %
22984-54-9	Methyl Oximino Silane	1% - 5%
2224-33-1	Vinyl Oximino Silane	1% - 5%
1760-24-3	N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane	1% - 5%
63148-62-9	Dimethylpolysiloxane	10% - 30%
112945-52-5	Amorphous fumed silica	5% - 10%
64741-44-2	Distillates (petroleum), straight-run middle	5% - 10%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Comments	Treat according to person's condition and specifics of exposure.
Ingestion	Get medical attention.
Inhalation	Remove to fresh air. If symptoms persist, obtain appropriate medical attention.
Skin Contact	Remove from skin and immediately flush with water for 15 minutes. Get medical attention if irritation or ill effects develop or persist.
Eye Contact	Immediately flush with water for 15 minutes. Seek medical attention.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media	Carbon dioxide, dry chemcial, foam, water, water fog or spray
Unsuitable Extinguishing Media	None known
Auto-ignition Temperature	Not determined
Upper Explosive Limit (%)	Not applicable
Lower Explosive Limit (%)	Not applicable
Special Fire Fighting Procedures	Fire fighters should wear full protective clothing including self contained breathing apparatus.
Unusual Fire or Explosion Hazards	None known

Section 6. Accidental Release Measures

Steps to be taken in case	Observe all personal protection equipment recommendations. Pick up any
of spill or release	debris to prevent footing hazard. Local, state and federal regulations may
	apply to releases and disposal of this material, as well as those materials
	and items employed in cleanup of releases.

Section 7. Handling and Storage

Handling	Avoid eye contact. Avoid skin contact. Avoid breathing vapor.
Storage	Keep container closed and store in a cool, well ventilated area, away from water or moisture.
Other Precautions	Product evolves methyl ethyl ketoxime (MEKO) when exposed to water or humid air. Provide ventilation during use to control MEKO within the exposure guidelines or use respiratory protection.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	acgih TLV	OSHA PEL	STEL
	Methyl Oximino Silane	N/A	N/A	N/A

	Vinyl Oximino Silane	N/A	N/A	N/A
	N-beta-(aminoethyl)-gamma- aminopropyltrimethoxysilane	N/A	N/A	N/A
	Dimethylpolysiloxane	N/A	N/A	N/A
	Amorphous fumed silica	10 mg/m3	6 mg/m3	N/A
	Distillates (petroleum), straight-run middle	N/A	N/A	N/A
Personal Protective Equipment	Goggles, Gloves			
Eye Protection	Safety goggles or glasses with side shields are recommended.			
Skin Protection	Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.			
	Suitable Gloves: Silver Shield® 4H®			
Ventilation	Good general ventilation should be sufficient.			
Respiratory Protection	If engineering controls do not maintain airborne ingredients below TLV, then a NIOSH/MSHA app should be used. Not required under normal usage	oroved organi	c vapor resp	oirator
Ingestion	Do not eat, drink or smoke during work.			

Section 9. Physical and Chemical Properties

Paste
Red
Slight
N/A
Insoluble
N/A
35 g/L
1,000,000
cPs
1.395978
11.65
87.14806
Not
Determined
N/A
Not
applicable
Not
determined
Not
determined
N/A
N/A
N/A

Evaporation Rate	Not determined
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	Not determined
Vapor Density	Not determined

Note

The above information is not intended for use in preparing product specifications. Contact Soudal Accumetric before writing specifications.

Section 10. Stability and Reactivity

Materials to Avoid /	None known
Incompatibility	
Conditions to Avoid	None known
Hazardous polymerization	Will not occur
Chemical Stability	Stable

Section 11. Toxicological Information

Component Toxicology No known applicable information. Information Special Hazard Information No known applicable information. on Components

Section 12. Ecological Information

Fate and Effects in Waste Water Treatment Plants	Complete information is not yet available.
Environmental Fate and Distribution	Complete information is not yet available.
Environmental Effects	Complete information is not yet available.

Section 13. Disposal

Waste Disposal Method	We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.
	This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Section 14. Transport Information

UN Number	N/A
UN Proper Shipping Name	Not regulated
DOT Classification	Not regulated
Packing Group	Not regulated
Ocean Shipment (IMDG)	Not subject to IMDG code.
Air Shipment (IATA)	Not subject to IATA regulations.

Section 15. Regulatory Information

	The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.
TSCA Status	All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.
California Proposition 65	This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: None known
SARA Title III Section 302 Extremely Hazardous Substances	None
SARA Titre III Section 304 CERCLA Substances dangereuses	None
SARA Title III Section 313 Toxic Chemicals	None present or none present in regulated quantities.
Massachusetts	Silica, amorphous fumed (112945-52-5)
New Jersey	Hydroxy-terminated polydimethylsiloxane (70131-67-8) Calcium carbonate (1317-65-3) Polydimethylsiloxane (63148-62-9) Silica, amorphous fumed (112945-52-5) Methyloximinosilane (22984-54-9)
Pennsylvania	Hydroxy-terminated polymethylsiloxane (70131-67-8) Calcium carbonate (1317-65-3)

Section 16. Other Information

Revision Date	11/10/2015
Disclaimer	The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.