

# AprilAire<sup>®</sup>

## Thermostat

### SPECIFICATION SHEET

## 8600 Series IAQ Controls



### Features:

- Real Language Programming – No Codes to Remember, No Manual to Reference
- Large 4.5" diagonal touch screen
- High and low balance point (requires 8052 outdoor temperature sensor, included)

- Maintenance Reminders
- Programmable Fan and Circulate Fan Mode
- Free Custom Imprinted Covers



Download the AprilAire  
Wi-Fi Thermostat App



## PROGRAMMABLE



### 8600

Universal 2H/2C  
or 4H/2C HP  
Touch Screen



### 8620

Universal 2H/2C or 4H/2C HP  
Event-Based™ Air Cleaning  
Humidity or Ventilation  
Touch Screen  
Includes Outdoor  
Temperature Sensor



### 8620W

Universal 2H/2C or 4H/2C HP  
Event-Based™ Air Cleaning  
Humidity or Ventilation  
Wi-Fi  
Touch Screen  
Includes Outdoor  
Temperature Sensor

## EASY TO INSTALL & MAINTAIN

- Water panel, air filter, dehumidifier and HVAC service indicators
- Dual Powered (choice of battery-powered or hardwired, for all applications)  
**Models 8600, 8620**
- Easy-to-wire terminal block
- Universal 2H/2C Conventional and 4H/2C Heat Pump
- Configurable heating and cooling, heating only or cooling only operation
- Remote indoor temperature available with optional 8051 flush mount or 8053 surface mount sensors
- Dual fuel operation built-in (auto lock-out of compressor with call for fossil fuel aux heat)
- Adjustable differential for 1st, 2nd, 3rd and 4th stage
- Configures as manual heat/cool, or with auto changeover

## ENGINEERED FOR EXCELLENCE

- Millivolt compatible
- High and low balance point (requires 8052 outdoor temperature sensor, included)
- Display temperature offset ( $\pm 4^{\circ}\text{F}$ )
- Multiple hold options maximizes comfort and energy savings
  - Vacation hold
  - Customizable timed hold
  - Permanent hold
- 5-year warranty
- **Models 8620 & 8620W Only**
- Whole-Home Comfort Control
- Humidity Control: Displays Indoor RH on User Interface
- Fresh Air Ventilation: Can be set up to use ASHRAE 62.2 guidelines
- Air Cleaning: Event-Based™ Air Cleaning
  - Constant Cleaning 24/7
  - Automatic (30 min/hr)
  - Event Clean (3 hr cycle)
  - Allergy (24 hr cycle)

## EASY & CONVENIENT TO USE

- Displays room temperature, temperature setting and outdoor temperature simultaneously. (Outdoor temperature display requires 8052 outdoor temperature sensor.)
- Large 4.5" diagonal LCD with high contrast for easier reading
- Bright, white backlit display with constant low intensity light option
- "Copy" function for quick and easy programming
- Real time clock automatically adjusts for daylight savings time
- Exclusive message center (provides feedback and real language instructions)
- Full or limited screen lockout
- Progressive recovery
- Built-in equipment protection
- Equipment stage indication
- Permanent memory – programming and custom schedules are not lost during a power outage. Time and date are restored with Wi-Fi connection

# 8600 Series IAQ Controls

## DIMENSIONS

6.00" x 4.85" x 1.25"

### Accessories

- 8052 Outdoor Temperature Sensor (included with Models 8620/8620W)
- 8051 Flush Mount Indoor Temperature Sensor
- 8053 Surface Mount Indoor Temperature Sensor



Model  
8052 Shown

## THERMAL SPECIFICATIONS

- **Control range**  
45° to 99°F (7° to 32°C)
- **Display range**  
32° to 99°F (0° to 40°C)
- **Accuracy**  
± 1°F (± .5°C)
- **Storage temperature**  
-30° to 140°F (-34.4° to 60°C)
- **Operating humidity**  
5% to 90% relative humidity
- **Operating ambient temperature of ECM**  
32° to 120°F (0° to 48.9°C)
- **Shipping temperature range**  
-30° to 140°F (-34.4° to 60°C)

## ELECTRICAL SPECIFICATIONS

- 24 VAC (18-30 VAC)
  - 1 amp maximum load per terminal
  - 2.5 amp total maximum load (all terminals)
    - **AC Power:** 18-30 Volt AC
    - **DC Power:** 3.0 Volts DC (2 "AA" Alkaline batteries included w/**Models 8600 & 8620**)
  - Millivolt systems
- Terminal Designations:**
- C, B, O, Y, Y2, G, RC, R, W2, W, L, S2, S1, T1, T2  
Models 8620 & 8620W also have I1 & I2

