





WELLXTROL

Next Generation Well Tanks Featuring Antimicrobial Protection

Specifications



WX-101 through WX-200



WX-201 through WX-350

Model Number	Tank Volume (Gallons)	Max. Acceptance Factor	Dimensions		System Conn. (Inches)	Drawdown (Gallons)			Shipping Weight (lbs.)
			A Diameter (Inches)	B Height (Inches)		30/50 (psig)	40/60 (psig)	50/70 (psig)	
WX-101	2.0	0.45	8	13	¾ NPTM	0.6	0.6	0.5	5
WX-102	4.4	0.55	11	15	¾ NPTM	1.4	1.2	1.0	9
WX-103	7.4	0.43	11	22	¾ NPTM	2.4	2.0	1.8	15
WX-104	10.3	1.00	15	18	1 NPTM	3.2	2.8	2.4	20
WX-200	14.0	0.81	15	22	1 NPTM	4.3	3.8	3.3	22
WX-201	14.0	0.81	15	25	1 NPTF	4.3	3.8	3.3	25
WX-202	20.0	0.57	15	32	1 NPTF	6.2	5.4	4.7	32
WX-202XL	26.0	0.44	15	39	1 NPTF	8.0	7.0	6.1	39
WX-203	32.0	0.35	15	47	1 NPTF	9.9	8.6	7.6	47
WX-205	34.0	1.00	22	30	1 ¼ NPTF	10.5	9.1	8.0	57
WX-250	44.0	0.77	22	36	1 ¼ NPTF	13.6	11.8	10.4	65
WX-251	62.0	0.55	22	47	1 ¼ NPTF	19.2	16.6	14.6	87
WX-255	81.0	0.41	22	57	1 ¼ NPTF	25.0	21.7	19.1	109
WX-252	86.0	0.39	22	62	1 ¼ NPTF	26.6	23.0	20.3	107
WX-302	86.0	0.54	26	47	1 ¼ NPTF	26.6	23.0	20.3	106
WX-350	119.0	0.39	26	62	1 ¼ NPTF	36.8	31.9	28.1	146

Stainless Steel System Connection.

Maximum Working Pressure: All models except WX-252: 150 psig. WX-252: 100 psig. Factory Precharge: 38 psig.

Drawdown can be affected by various ambient and system conditions, including temperature and pressure.

Well-X-Trol® ESP Quick Sizing Table

Pump Discharge Rate (Approx. GPM)	Pumps Up To 3/4 hp & 1 Minute Run Time			Pumps Over 3/4 hp & 2 Minute Run Time		
	30/50 psig	40/60 psig	50/70 psig	30/50 psig	40/60 psig	50/70 psig
5	WX-202	WX-202	WX-202	WX-205	WX-205	WX-250
7	WX-202XL	WX-202XL	WX-203	WX-250	WX-251	WX-251
10	WX-203	WX-205	WX-250	WX-251	WX-255	WX-302
12	WX-250	WX-250	WX-251	WX-255	WX-255	WX-350
15	WX-250	WX-251	WX-251	WX-302	WX-350	WX-350
20	WX-251	WX-255	WX-302	WX-350	WX-255 (2)	WX-302 (2)
25	WX-255	WX-302	WX-350	WX-255 (2)	WX-302 (2)	WX-350 (2)
30	WX-302	WX-350	WX-350	WX-302 (2)	WX-350 (2)	WX-302 (3)
35	WX-350	WX-350	WX-255 (2)	WX-350 (2)	WX-350 (2)	WX-350 (3)
40	WX-350	WX-255 (2)	WX-302 (2)	WX-350 (2)	WX-302 (3)	WX-350 (3)

The Effective System Protection (ESP) sizing procedure covers modern residential water use habits, heavy demands and the general pressure increase that has occurred in recent years. ESP sizing is designed to reduce system wear and lower energy consumption by keeping pump starts to a minimum.

Larger Tank = Fewer Cycles = Longer Tank and Pump Life.



Antimicrobial.



Turbulator.



NSF/ANSI 61



www.amtrol.com

