


RIBXGTV10

MULTI-RANGE SPLIT CORE AC TRANSDUCER



ı	DIP SWITCH		RANGE
	1	2	
ı	OFF	0FF	0-20A
ı	OFF	ON	0-50A
ı	ON	OFF	0-100A

CONTROL UNIT
ACCESSORIES
also suitable for use as:
ENCLOSED ENERGY
MANAGEMENT EQUIPMENT, SMOKE CONTROL,
SIGNAL APPLIANCES

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.


Bulletin B1413





RIBXGTV10

MULTI-RANGE SPLIT CORE **AC TRANSDUCER**

Squeeze the locking tabs, then pull up and back to open.







Wire Clamp

Output (Terminals) Removable Mounting Tab

Dip Switches

Operating Temperature: -30 to 140° F

Max Sense Voltage: 600 Vac

Approvals:

UL Listed, UL916, UL864, C-UL Canada, CE

> **Housing Rating:** Plenum, NEMA 1



Functional Devices, Inc. 310 South Union Street Russiaville, IN 46979

www.FunctionalDevices.com

Bulletin B1413