# HBV2 LF/HBVAF2 LF/HBDUC/LF

38-300/38LF-300/38LF-40D Series Hose Connection Vacuum Breakers





Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO#:	
Rep:	
Wholesale Dist.:	

#### DESCRIPTION

The Apollo\* Models HBV2 LF, HBVAF2 LF, HBDUC, and HBDUC LF Hose Connection Vacuum Breakers are designed to prevent cross-connection caused by back-siphonage. The Apollo\* Model HBDUC Hose Bibb Dual Check Backflow Preventer also prevents backflow due to low head back-pressure.

### FEATURES HBV2 LF(38LF-314)

- · Tamper-Proof Protection
- · Corrosion Resistant
- · Manual Drain Feature
- Apollo International™
- Lead Free to NSF/ANSI 372

#### HBVAF2 LF (38LF-414)

- · For Wall And Yard Hydrant Application
- Tamper-Proof Protection
- Corrosion Resistant
- Lead Free to NSF 372
- Anti-Freeze Automatic Drain Feature
- Apollo International™

## HBDUC (38/38LF-304-02)

- Corrosion Resistant Body and Checks
- Low Head Loss
- · Easy to Install with Break-Away Set Screw
- · Made in USA
- · Lead Free Options Available

## **PERFORMANCE RATING**

- Maximum Supply Pressure:
  125 psi (38-314/414)
  150 psi (38-304-02)
- Temperature Range: 33°F 180°F

#### **APPROVALS**

- ASSE 1011, CSA B64.2 and IAPMO Listed (38LF-314/414)
- ASSE 1052 and CSA B64.2 Listed (38/38LF-304-02)

## STANDARD MATERIALS LIST

HBV2/HBVAF2				
BODY	Brass			
CHECK DISC/DIAPHRAGM	Buna N			
SPRING	Stainless Steel			
HBDUC				
BODY	Brass			
SEATS	EPDM			
CHECK COMPONENTS	Stainless Steel			
CHECK GUIDE	Acetal			

## **DIMENSIONS**


	MODEL	PART	DIMENSIONS (IN.)		WT (LD)
ı	NUMBER	IUMBER NUMBER	Α	В	WT. (LB.)
	HBV2-34	38-314-AS	1-1/4	1-1/4	0.15
	HBVAF2-34	38-414-AS	2	1-3/8	0.25
	HBDUC-34	38-304-02	2-11/16	1-5/16	0.46

#### **MODEL NUMBER MATRIX**


38LF	- X 14	- X X	
	SERIES	FINISH	
	3 - 300 SERIES (3/4" HOSE CONNECTION)	AS - SATIN BRASS	
	4 - 400 SERIES (3/4" HOSE CONNECTION)	CS - SATIN CHROME (HBV2 ONLY)	

#### PART NUMBER MATRIX \*Satin Brass Finish Only\*

38/38LF	- 304	- 02	
	SERIES	FINISH	
	3 - 300 SERIES (3/4" HOSE CONNECTION)	AS - SATIN BRASS	



## **FLOW CURVE**



\*LEAD FREE: The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with Federal Public Law 111-380. ANSI 3rd party approved and listed.