



MANAGED PROPERTY THERMOSTATS

One-time configurable with patent-pending technology to deter tenants from tampering!

Why waste time and money installing dummy thermostats or cases that can be broken into?

ICM Controls' new line of Managed Property Thermostats give landlords peace of mind knowing that their profits are safe from tenants who like to "tamper" with their thermostat set points, often resulting in unsuspected, skyrocketing utility costs. Each model features digital accuracy with one-time configurable heat/cool set point limits that cannot be reconfigured.

Multiple models to choose from!



- One-time configurable temperature minimum/maximum set points
- Patent-pending Abnormal Rate of Change (ARC) Detection technology
- Placebo option
- 7-Day, 5-2 day, and 5-1-1 day programming (programmable models only)
- Auto and/or manual changeover
- Large, digital backlit display
- Selectable °F and °C
- Precise temperature sensing (accuracy $\pm 1^\circ\text{F}$)
- Patented Thermal Intrusion Barrier
- Permanent memory
- Adjustable temperature differential
- Easy-access terminal block
- Integrated 4-minute short-cycle timer
- Soft-touch controls
- Status LEDs (all models but MP2010L)
- Mercury-free, environmentally safe





SPECIFICATIONS







Electrical Rating: 24 VAC (18-30 VAC)

- 1 amp maximum per terminal
- 3 amp maximum total load (4 amps on multiple-stage units)

Temperature control ranges:

- 45°F to 75°F Heat (7°C to 24°C)
- 70°F to 90°F Cool (21°C to 32°C)

ORDERING INFORMATION

| | Model # | Type | Stages | Changeover | Power | Remote Sensor Compatible | Terminations |
|--|---------|------------------|-----------------|-------------|-------|--------------------------|--|
|  | MP2010L | Non-Programmable | 1H/1C or 1HP | Manual | Dual | N | RC, RH, C, W, Y, O, B, G |
|  | MP2211L | Non-Programmable | 3H/2C HP Only | Manual | HW | N | R, C, Y1, Y2, W2, O, B, G, E, L, W3 |
|  | MP4010 | Non-Programmable | 1H/1C or 1HP | Auto/Manual | Dual | Y | RC, RH, C, W/O/B, Y, G, S1, S2 |
|  | MP4211 | Non-Programmable | 2-Stage HP Only | Auto/Manual | HW | Y | R, C, Y1, Y2, W2, O/B, G, E, L, S1, S2 |
|  | MP5010 | Programmable | 1H/1C or 1HP | Auto/Manual | Dual | Y | RC, RH, C, W/O/B, Y, G, S1, S2 |
|  | MP5211 | Programmable | 2-Stage HP Only | Auto/Manual | HW | Y | R, C, Y1, Y2, W2, O/B, G, E, L, S1, S2 |

FOLLOW US ON:



Customized settings also available for volume orders. Call our factory Tech Support Department at 800.365.5525 ext. 375 for more information. Or, contact your local **ICM Controls** Sales Representative.

Specifications subject to change without notice.

Patent No. Design: 424, 953

Patent No. Thermal Intrusion Barrier: 6, 597, 275

800.365.5525

www.icmcontrols.com

LIS234