

Compass

REFRIGERANT LEAK DETECTOR

Locate the leak with proven sensor technology.

Compass takes the proven heated diode sensor of TEK-Mate and adds premium features like a rubber hand grip and rechargeable battery. Get improved sensitivity from the probe tip-mounted sensor. Compass can even be operated while charging with the included car and wall chargers.



ADVANTAGES

- Sensitivity of 0.15 oz./year (4 g/year)
- Detects all CFCs, HCFCs, HFCs, and HFOs
- Proven heated diode sensor for reliable leak checking
- No false alarms from soap solutions
- Runs on rechargeable battery or AC adapter
- Advanced filter keeps out water, dirt, and oil
- Rugged carrying case included

SPECIFICATIONS

| | |
|-------------------------------|--|
| Includes | Compass Heated diode sensor NiMH rechargeable battery Spare filters AC wall charger DC car charger Carrying case |
| Compatible refrigerants | R22, R32, R134a, R404a, R407c, R410a, R422b, R448a, R449a, R452a, R452b, R507 (AZ50), R1234yf and more |
| Minimum sensitivity | 0.15 oz./yr. (4 g/a) |
| Power source | NiMH battery (rechargeable) Wall/car charger (can operate while charging) |
| Battery life | 5.5 hours |
| Weight | 1.15 lb. (522 g) |
| Certifications | CE |
| Probe length (standard probe) | 15 in. (38 cm) |
| Warranty | Two-year, over-the-counter |

ORDERING INFORMATION

| | |
|--|-------------|
| Compass (115 V) | 717-202-G1 |
| Accessories and Replacement Parts | |
| Headphones | 032-0430 |
| Premium headphones | 032-0427 |
| TEK-Check R134a reference leak | 703-080-G10 |
| 115 V (ac) wall charger | 033-0019-G1 |
| 12 V (dc) car charger | 703-055-P1 |
| NiMH battery | 712-700-G1 |
| Sensor | 703-020-G1 |
| Filters | 717-701-G1 |
| Carrying Case | 717-700-G1 |