

WIFI MADE SIMPLE

PRU

A THERMOSTAT COMPANY **DESIGNED FOR THE PROFESSIONAL TRADE**



High Quality U

 (\mathbf{J})

PRO1 thermostats are professional grade, built on proven performance and reliability. It's a difference you can see and feel.

One Size Thermostats

All PRO1 thermostats have the same size footprint, so you never have to worry about wall marks left by old models. You can also upgrade to new models including WIFI without rewiring using the interchangeable subbase system.

Full Offering (\mathbf{l})

> We offer a full line of thermostats for nearly every application. Whether you need a basic 1 heat, 1 cool non-programmable or a 4 heat, 2 cool WIFI thermostat, PRO1 has you covered.

Badge System (\mathbf{J})

PRO1 pioneered the free and simple Private Label Program to make your brand the focus. Other companies provide some version of customization, but no other thermostat manufacturer removes their branding altogether. At PRO1, we put YOUR brand front and center, where it should be.



EXCLUSIVELY FOR PROFESSIONALS







GET IT ON

Google Play is a trademark of Google Inc.

Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark

THE POWER OF PARTNERSHIP

www.proliaq.com

1-888-PRO1-IAQ (776-1427)



SIMPLE. AFFORDABLE. PROFESSIONAL.

The industry's simplest private label program just got

BRIGHTER.





C 7D 5/1/1 NP	Commercial Time Periods (Occupied/Unoccupied) 7 Day Programmable 5/1/1 Programmable Non-Programmable	Stages of Heat	Stages of Cool	Gas, Electric or Oil	Heat Pump with Auxiliary	Heat Pump without Auxiliary	PTAC Mode	Battery Power	120 Line Voltage	24V Power (Hardwire)	Outdoor Temperature Sensor Compatible	Dual Fuel Compatible	Display Size (Square Inches)	Auto Changeover	Filter Change Reminder	Room Temperature Calibration	Minimum Compresso Run Time	Compressor Short Cycle Delay	Adjustable Heat & Co Temperature Swing	Cooling Fan Delay	Ventilation Control	Programmable Fan	Pre-Occupancy Fan Purge	IAQ Fan Mode	
------------------------	--	----------------	----------------	----------------------	-----------------------------	--------------------------------	-----------	---------------	------------------	----------------------	--	----------------------	---------------------------------	-----------------	---------------------------	---------------------------------	-------------------------------	---------------------------------	---	-------------------	---------------------	------------------	----------------------------	--------------	--

	PRU) B			 Commercial Time Periods (Occupied/Unoccupied) 7 Day Programmable 5/1/1 5/1/1 Programmable NP Non-Programmable 	Stages of Heat	Stages of Cool	Heat Pump with	Auxiliary Heat Pump without Auxiliary	PTAC Mode	Battery Power 1201 ine Voltage	24V Power (Hardwire)	Outdoor Temperature Sensor Compatible	Dual Fuel Compatible	Display Size (Square Inches)	Auto Cnangeover Filter Change	Reminder Room Temperature Calibration	Minimum Compressor Bun Time	Compressor Short Cycle Delay	Adjustable Heat & Cool Temperature Swing	ooling Far	Ventilation Control Programmable Fan	Pre-Occupancy Fan Purge	IAQ Fan Mode	Always on Uisplay Light Keypad Lockout	Adjustable Setpoint Limits	Humidity Control Memory Type	Touchscreen	Remote Sensor Capable	Millivolt	Warranty	Terminals
	Accessories																															
Model Z2K955WDA	Description Two Zone Kit	Compatible With Zoning Models		Pro1 Model # T855iSH	7D NP C	5*	3* •	•	•	•		•	•	•	8	• •	• •	•	•	•	•	• •	•	•	• •	•	• •		•	•	5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O, S1, S2, H, D
	Secondary Zone Controller / Wireless		HI	T721i	7D **	2*		• •	•			•		•	4		•		•	•					•	•	•			•	_	R, C, Y, W2, W/E, G, O, B
RZ251W	Controller / Wireless Remote Sensor	Z955W T955WH	>	T701i	7D **	1	1.	,	•			•			4		•		•	•					•	•	•			•	5	Rh,Rc,C,Y,W/E,W2,G,0,B
RZ250W	Wireless Outdoor Sensor	Z955W T955WH		T955WH	7D 5/1/1 NP C	3*	2 •	•	•		•	•	•	•	13	• •	• •	•	•	•	•	•	•		• •	•	• •	•	•		5	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B, H, D
Z260W	Wireless Damper Module	Z955W	ELESS	T731W	NP	2*	1.			•	•	•			7		•		•	•					•	•	•			•		R, C, Y, W, GL, GH, O, B
ZDA250W	Wireless Discharge Air Sensor	Z955W	WIR	T731WO	NP	2*	1 •		•	•	•	•			7		•		•	•					•	•	•			•		R, C, Y, W, GL, GH, O, B
W150W	Wireless Repeater	Wireless Models		T955	7D 5/1/1 NP C	3*	2 •	• •	•		•	•		•	13	• •	• •	•	•	•	•	•	•	•	• •	•	•	•		•		Rh, Rc, C, Y, Y2, W/E, W2, G, O, B
R250S	Wired Outdoor	T755S T855SH				5*				•	•	•			_			•							• •		• •		•	•	5	
N2303	Temperature Sensor	T955S	BETTER	T855SH T855	7D 5/1/1 NP C 7D 5/1/1 NP C	3*	5		_	•	•	•	•	•	•	• •	-	•	•	•		• •	-		• •		• •			•		Rh, Rc, C, Y, Y2, W/E, W2, G, B, O, S1, S2, H, D Rh, Rc, C, Y, Y2, W/E, W2, G, O, B
R251S	Wired Indoor Temperature Sensor	T755S T855SH T955S	BEI	T805	7D 5/1/1 NP	1	1 •	_	•		•	•		•	-	• •	_	•	•	•	•	• •			• •		•			•		Rh, Rc, C, Y, W, G, O, B
T150	Stat Guard Cover	Any		T771	NP	0/1	0/1 •				•	•			4		•		•	•						•	•			•		R, C, W/Y, G
		Thermostat Any		T755S	7D 5/1/1 NP	3*		• •	•	•	•	•	•	•		• •	_	•	•	•	•	•			•	•	•		•	•	5	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B, S1, S2
T119	Universal Wall Plate	Thermostat		T755	7D 5/1/1 NP	3*	_		•	•	•	•		•	-	• •	• •	•	•	•	•	•			•	•	•			•	5	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B
E219	Weather Resistant Junction Box	Any Thermostat		T751	NP	3*		• •	•	•	•	•		•	7	• •	• •	•	•	•	•				•	•	•			•	5	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B
Мос	del # Nomencla	ture		T731	NP	2*	1.		•	•	•	•			4		•		•	•					•	•	•			•	_	R, C, Y, W, GL, GH, O, B
Prefix			B	T725	7D 5/1/1 NP	2*	1 •	• •	•		•	•		•	4	•	• •		•	•						•	•			•	5	R, C, Y, W2, W/E, G, O, B
T - Thermostats R - Remote Sens		harge Air Sensor ing Capable	Ŭ	T721	NP	2*	1 •	• •	•		•	•		•	4		•		•	•						•	•			•	5	R, C, Y, W2, W/E, G, O, B
First Number				T715	7D 5/1/1 NP	2	2 •	•	•		•	•			4	•	• •		•	•						•	•			•	5	Rh, Rc, C, Y, Y2, W, W2, G, O, B
5 - 500 Platform 6 - 600 Platform				T705	7D 5/1/1 NP	1	1 •	•	•		•	•	\square		4	•	• •		•	•						•	•			•	5	Rh, Rc, C, Y, W, G, O, B
7 - 700 Platform Second Number	l			T701	NP	1	1 •	•	•		•	•			4		•		•	•						•	•			•	5	Rh, Rc, C, Y, W, G, O, B
0 - Single Stage 1 - Multi Stage G		rsal PTAC rsal Multi Stage		T625-2	7D 5/1/1	2*	1 •	• •	•		•	•		•	2		•		•	•						•	•			•	2	R, C, Y, W2, E, G, O, B
	Heat Pump 7 - Heatin		E	T621-2	NP	2*	1 •	• •	•		•	•		•	2		•		•	•						•	•			•	2	R, C, Y, W2, E, G, O, B
Third Number			BUIL	T605-2	7D 5/1/1	1	1 •	•	•		•	•			2		•		•	•						•	•			•	2	Rh, Rc, C, Y, W, G, O, B
1 - Non-Programmable 5 - Programmable				T601-2	NP	1	1 •		•		•	•			2		•		•	•						•	•			•	2	Rh, Rc, C, Y, W, G, O, B
Suffix W - Wireless	S - Wired	Remote Sensor	Ę	T501ML4	NP	1	0				•																				2	4 Wire
H - Humidity Co i - Internet Capa	ontrol 0 - Occup	bancy Sensor	HANK	T501ML2	NP	1	0				•																				2	2 Wire
M - Mechanical			MECI	T501M	NP	1	1•		•																					•	2	Rh, Rc, Y, W, G, O, B

Stages* = One less stage for conventional heat and cool *Programming** = Can only be modified through the app.*

www.proliaq.com

THE POWER OF PARTNERSHIP

1-888-PRO1-IAQ (776-1427)