

SPECIALTY TAPES FROM INTERTAPE®



With a wide variety of HVAC/R applications, SUPCO® has got you covered!

AC698 Premium BOPP Film HVAC Tape. UL® Listed. 181B-FX



PART NUMBER	COLOR	DIMENSIONS	BACKING	ADHESIVE	TEMP.	MIN/MULTI
89306	Silver	1.88" x 359'	40 micron BOPP	Emulsion Acrylic	-65°F to 212°F	24
89307	Black	1.88" x 359'	40 micron BOPP	Emulsion Acrylic	-65°F to 212°F	24

AC50-UL 14 Mil Cloth Duct Tape. UL Listed®. 181B-FX



PART NUMBER	COLOR	DIMENSIONS	BACKING	ADHESIVE	TEMP.	MIN/MULTI
99521	Silver	1.88" x 179'	PE Film	Rubber/Resin	32°F to 200°F	24
99522	Black	1.88" x 179'	PE Film	Rubber/Resin	32°F to 200°F	24
99540	Metalized	1.88" x 179'	PE Film	Rubber/Resin	32°F to 200°F	24

AC36 11 Mil Medium Grade Duct Tape



PART NUMBER	COLOR	DIMENSIONS	BACKING	ADHESIVE	TEMP.	MIN/MULTI
4137	Silver	1.88" x 179'	PE Film	Rubber/Resin	32°F to 180°F	24
4382	Black	1.88" x 179'	PE Film	Rubber/Resin	32°F to 180°F	24

AC20 9 Mil Utility Duct Tape



PART NUMBER	COLOR	DIMENSIONS	BACKING	ADHESIVE	TEMP.	MIN/MULTI
91407	Black	1.88" x 179'	PE Film	Rubber/Resin	32°F to 160°F	24
91410	Silver	1.88" x 179'	PE Film	Rubber/Resin	32°F to 160°F	24

ALF Mastic Specialty Mastic Foil Tape. Tested to UL-723




PART NUMBER	DIMENSIONS	BACKING	ADHESIVE	TEMP.	MIN/MULTI
99631	2" x 100'	Aluminum	Acrylic	-30°F to 350°F	12
99632	3" x 100'	Aluminum	Acrylic	-30°F to 350°F	12

ALF201L-UL 2 Mil Premium Aluminum Foil Tape. UL® Listed UL181A-P and UL181B-FX



PART NUMBER	DIMENSIONS	BACKING	ADHESIVE	TEMP.	MIN/MULTI
ALF201LUL2560HR	2 ½" x 60 yd	Aluminum Foil	Acrylic	-30°F to 350°F	16
ALF201LUL360HR	3" x 60 yd	Aluminum Foil	Acrylic	-30°F to 350°F	16

ALF175L Medium Grade "Cold Temp" Aluminum Foil Tape. Tested to UL-723



PART NUMBER	DIMENSIONS	BACKING	ADHESIVE	TEMP.	MIN/MULTI
ALF175L0250HR	2" x 50 yd	Aluminum Foil	Acrylic	-58°F to 200°F	24
ALF175L0350HR	3" x 50 yd	Aluminum Foil	Acrylic	-58°F to 200°F	16

FSK1 Foil- Scrim- Kraft Specialty Tape. Tested to UL-723



PART NUMBER	DIMENSIONS	BACKING	ADHESIVE	TEMP.	MIN/MULTI
99608	3" x 50 yd	Foil/Scrim/Kraft	Acrylic	-30°F to 350°F	12

Thread Sealing Tape



PART NUMBER	COLOR	DIMENSIONS	BACKING	TEMP.	MIN/MULTI
TS260	White	½" x 260"	Virgin PTFE film	-400°F to 700°F	200
TS520	White	½" x 520"	Virgin PTFE film	-400°F to 700°F	200

607 Medium Grade Vinyl Electrical Tape



PART NUMBER	DIMENSIONS	BACKING	ADHESIVE	MAX TEMP.	MIN/MULTI
85835	¾" x 66'	PVC film	Rubber/Resin	176°F	120

82758

AC50 Spray Adhesive 12 oz.
Complies with National VOC Regulations
Min/Multi: 12



99622 Measure-It Tape

The measuring tape that sticks!



- Repeating 12" measure
- Paintable & markable
- 16" "on center" stud marks
- Low tack
- 1" x 48'
- Min/Multi: 24