



1F95U-42WF



1F95U-42WFB

Sensi Touch Smart Thermostat

Easy install for you, upgraded features and convenient comfort for your homeowners. It's contractor-tested and homeowner-approved.

Sensi Partners get access to program benefits including homeowner leads, contractor branding, custom literature and free online training. Learn more at emerson.com/sensipartner



Easy to install & connect

Features illuminated easy-click terminals and in-app instructions.



Contractor mode

With Contractor Mode, you can easily connect to every customer by registering thermostats individually or in batches.



Contractor-on-call

Be the contractor on call in customers monthly usage reports, service reminders, smart alerts and in-app. Register at sensiregistration.com



Smart alerts

Notifies customers of extreme temperature and humidity levels.



Humidity control

Help homeowners stay comfortable with humidification/dehumidification control.



Service reminders

Customers receive notifications when routine maintenance needs to be done. The Sensi app will remind them when it's time for a new air filter and other HVAC maintenance.



Save about 23% on HVAC energy¹

By adjusting the temperature using flexible scheduling, remote access, and geofencing, Sensi thermostat customers save about 23% on HVAC energy usage.



Usage reports

Monitor current day and historical heating, cooling and fan runtimes right in the app.



Circulating Fan

Air circulation may improve indoor air quality by helping to regulate temperature and prevent buildup of particles and mold.



Keypad lockout & temperature limits

Maintain total control by setting temperature limits and disabling changes by others at the thermostat



Smart home compatible

Compatible with smart home platforms Amazon Alexa, the Google Assistant, Apple HomeKit and SmartThings.



¹ Energy savings are calculated by comparing operation time for a nationwide sample of Sensi users with temperature adjustments averaging 4° in comparison to users with no adjustments. Savings vary based on equipment type/condition, insulation, climate & temperature adjustment size/frequency.

Use of the Works with Apple HomeKit logo means that an electronic accessory has been designed to connect specifically to iPod touch, iPhone, or iPad, respectively, and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards. Google is a trademark of Google LLC. A trademark of Reviewed.com Used under license; Reprinted with permission. Copyright 2020, Reviewed.com. All Rights Reserved



MAKING INSTALLATION EVEN EASIER

- Built-in level for picture-perfect mounting
- Terminal lights for increased visibility while wiring
- Large, easy-to-read terminal labels on the back plate
- Easy-click terminals, eliminating the need for a screwdriver
- Size that covers the existing footprint of most thermostats



SPECIFICATIONS

Electrical Rating

20 to 30 VAC, 50/60 Hz
 1.5 Amps maximum per terminal
 2.5 Amps maximum
 (all terminals combined)

Standard Systems

Single-stage gas, oil, electric
 Single-stage heat pump
 Multi-stage gas, oil, electric
 Multi-stage heat pump

Setpoint Range

45°F to 99°F (10°C to 36°C)

Accessories

Wallplate: (white) F61-2689 (6.75" x 4.50")
 Wallplate: (black) SA5B (6.75" X 4.50")
 Thermostat guard: F29-0198

Rated Differentials (@ 6°F / Hr)

Heat (conventional gas/oil/elect):
 Cool (central air):
 Heat pump (heat and cool):
 Heat pump (aux):

Compatibility

Conventional heating and cooling system:
 Apple HomeKit, heat pump*, heat only and cool only systems:

Sensi Alert

High temperature:
 Low temperature:
 High humidity:
 Loss of heat/cool:

	FAST	MED	SLOW
Heat (conventional gas/oil/elect):	0.5°F	0.75°F	1.9°F
Cool (central air):	0.9°F	1.2°F	1.7°F
Heat pump (heat and cool):	0.9°F	1.2°F	1.7°F
Heat pump (aux):	0.5°F	0.75°F	1.9°F

POWER SOURCE

Hardwired only (c-wire)
 Hardwired only (c-wire)

TRIGGER

Above 99°F
 Below 45°F
 Above 70%
 Temp goes up or down 5°F during cycle

Dimensions

5.625" W x 3.4" H x 1.00" D

Storage

-20° to 150°F (-29° to 65°C)
 0%-90% RH non-condensing

Operating Ambient

32°F to +105°F
 (0°C to +41°C)

Operating Humidity

90% non-condensing max

Display Temperature Range

32°F to +99°F (0°C to 37°C)

Title 24 Compliant

Energy Star Certified

*The Sensi thermostat provides automatic dual fuel control without an outdoor sensor. A fossil fuel kit may be added if user selectable balance point settings are desired.

MODEL NUMBER	PROGRAMS		STAGES BY SYSTEM			SYSTEM TYPE	APPLICATIONS					POWER SOURCE	SELECTABLE PERFORMANCE FEATURES								
	Program Options	Periods Per Day Options	Single Stage Heat/Cool	Multi-Stage Heat/Cool	Heat Pump Heat/Cool	Universal, Single Stage, Multi-Stage, Heat Pump*	Gas / Oil / Electric	3 Wire Zone Valve	Millivolt Compatible	Economizer	Humidity Control (H)-Humidity / (D)-Dehumidify	Dual Fuel Heat, Pump Control, Logic (L), Outdoor Sensor (O)	Remote Sensor Options, Indoor (I), Outdoor (O)	Battery (B), Hardwire / Common (H), Power Sharing (PS)	Auto Changeover	Programmable Fan (PF), Comfort Circulating Fan (CC)	Filter Change Reminder	Energy Mgt.-Recovery / Early Start	Total Keypad Lockout (T), Partial Keypad Lockout (P)	Set-Point Temperature Limits Adjustable Min/Max	Display Size, Backlight with Key Press (K), Continuous Backlight with Common (C)
1F95U-42WF, 1F95U-42WFB	7, NP, Geofencing	8 Max	1/1	2/2	4/2	Universal Sensi Touch	✓	✓	-	-	H, D	L	-	H	✓	CC	✓	✓	T	✓	8.0" Color

* Universal thermostats provide the flexibility to control Single Stage, Multi-Stage, or Heat Pump systems.

Terminal Designations



#Thermostat has internal jumper on RC and RH. On two transformer systems, clip red jumper wire on thermostat.

EMERSON.COM/SENSIPRO

The Sensi and Emerson logos are trademarks and service marks of Emerson Electric Co ©2020. All rights reserved. R-4569-13

